

# CASE WHEELED LOADERS 921B CUMMINS

## LTA 10C (1994-1998)



**ENGINE** Cummins LTA10C  
Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Change every 250 hours*

**DIFFERENTIAL FRONT AND REAR**  
Capacity: 127 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140**

*Change every 1000 hours*

**TRANSMISSION**  
Capacity: 28,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

*Change every 1000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 228 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Change every 2000 hours*

**COOLING SYSTEM**  
Capacity: 47,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

# CASE WHEELED LOADERS 921B CUMMINS LTA 10C (1994-1998)



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*