

CATERPILLAR ASPHALT PAVERS AP/BG

AP-1000B AGP, 7HN

**ENGINE**

Capacity: 20 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Change every 250 hours/ 1 months***USE**

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40***Change every 250 hours/ 1 months***HUB REDUCTIONS**

Capacity: 5 liter (each hub)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 50***Change every 500 hours/ 3 months***HYDRAULIC SYSTEM**

Capacity: 189 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30***Change every 1000 hours/ 12 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak CVT 10W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Agrifluid HT-Plus***Change every 1000 hours/ 12 months*

CATERPILLAR ASPHALT PAVERS AP/BG

AP-1000B AGP, 7HN



COOLING SYSTEM

Capacity: 37 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Change every 6000 hours/ 72 months

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Change every 24 months/ 3000 hours

PUMP DRIVE UNIT

Capacity: 2,6 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours/ 12 months

REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S)

Capacity: 0,65-1 liter (each side)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Change every 500 hours/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.