

<b>ENGINE</b> C6.6 Acert Capacity: 15 liter			
use Normal		climate Mediterranean	
PRODUCT RECOMMENDATION 1  Agridiesel MSP 15W-40  Agridiesel CRD+ 15W-40		PRODUCT RECOMMENDATION 3  Multifleet SHPD 15W-40	
Change every 500 hours/ 3 months			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3  Armado Synth 10W-40	
Change every 500 hours/ 3 months	1	1	

DIFFERENTIAL FRONT Capacity: 11 liter			
USE		CLIMATE	
Material Handler		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Change every 1000 hours/ 12 months			
USE		CLIMATE	
Travelling time > 25% of operating hours		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Change every 1500 hours/ 12 months			
USE		CLIMATE	
Travelling time < 25% of operating hours		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT	
Change every 2000 hours/ 12 months			



<b>DIFFERENTIAL REAR</b> Capacity: 14,5 liter		
USE		climate Moderate
Material Handler		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1000 hours/ 12 month	s	·
USE		CLIMATE
Travelling time > 25% of operating hours		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1500 hours/ 12 month	s	·
USE		CLIMATE
Travelling time < 25% of operating hours		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 2000 hours/ 12 month	S	'

FINAL DRIVES Capacity: 2,5 liter		
USE		CLIMATE
Material Handler		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1000 hours/ 12 months		
USE		CLIMATE
Travelling time > 25% of operating hours		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 1500 hours/ 12 months		·
USE		CLIMATE
Travelling time < 25% of operating hours		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Change every 2000 hours/ 12 months	1	

TRANSMISSION Capacity: 2,5 liter



USE		CLIMATE
Material Handler		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours/ 12 months		
JSE		CLIMATE
Material Handler		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 1000 hours/ 12 months		
JSE		CLIMATE
Travelling time > 25% of operation	ng hours	Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1500 hours/ 12 months		
USE		CLIMATE
Travelling time > 25% of operation	ng hours	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 1500 hours/ 12 months		
USE		CLIMATE
Travelling time < 25% of operation	ng hours	Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 2000 hours/ 12 months		
USE		CLIMATE
Travelling time < 25% of operatii	ng hours	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 2000 hours/ 12 months		
HYDRAULIC SYSTEM Capacity: 225 liter (Hydraulic tank), Ca	anacity: 250 litar (Tatel)	
Capacity. 225 liter (Hydraulic tank), Ci	apacity. 330 liter (Total)	

HYDRAULIC SYSTEM Capacity: 225 liter (Hydraulic tank), Capacity: 350 liter (Total)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 30	Gear Oil Alcat 30		
Change every 2000 hours/ 12 months			



Agridiesel CRD+ 15W-40 Agrifluid HT-Plus  Change every 2000 hours/ 12 months	
Change every 2000 hours/ 12 months	s Kroontrak MTH 10W-30
IISE	
002	CLIMATE
50% use of breaker	Mediterranean
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDA	ATION 2
Multifleet SCD 30 Gear Oil Alcat 30	)
Change every 1000 hours	·
USE	CLIMATE
50% use of breaker	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDA	ATION 2 PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40 Agrifluid HT-Plus	s Kroontrak MTH 10W-30
Change every 1000 hours	·
USE	CLIMATE
100% use of breaker	Mediterranean
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDA	ATION 2
Multifleet SCD 30 Gear Oil Alcat 30	)
Change every 600 hours	
USE	CLIMATE
100% use of breaker	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDA	ATION 2 PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40 Agrifluid HT-Plus	s Kroontrak MTH 10W-30
Change every 600 hours	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
JSE	CLIMATE
Light Duty	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

PRODUCT RECOMMENDATION

### CATERPILLAR WHEELED EXCAVATORS M322D W2S, W2T (2005 AND AFTER)



COOLING SYSTEM Capacity: 33 liter	
USE	CLIMATE
Extended drain (max)	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Change every 12000 hours/72 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.