

CATERPILLAR MOTOR GRADERS 16G 59M

(1973-1995)



ENGINE 3406C
Capacity: 34 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	Multifleet SCD 30

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 10 hours, change every 1 months/ 250 hours

TANDEM DRIVE
Capacity: 125 liter (each side)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 50	Multifleet SCD 40

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

CATERPILLAR MOTOR GRADERS 16G 59M

(1973-1995)



TRANSMISSION Powershift
Capacity: 114 liter (+ differential)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM
Capacity: 114 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 10W		

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

CATERPILLAR MOTOR GRADERS 16G 59M

(1973-1995)



COOLING SYSTEM

Capacity: 79 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 2000 hours/ 12 months*

CIRCLE DRIVE UNIT

Capacity: 8 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 50

PRODUCT RECOMMENDATION 2

Multifleet SCD 40*Change every 2000 hours/ 12 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 2000 hours/ 12 months*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 2000 hours/ 12 months*

CATERPILLAR MOTOR GRADERS 16G 59M

(1973-1995)



WHEEL SPINDLE HOUSINGS FRONT

Capacity: 1 liter (each side)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Change every 500 hours/ 3 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Change every 500 hours/ 3 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 500 hours/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.