CATERPILLAR TRACKED EXCAVATORS 245 94L (TILL 1990)



ENGINE Capacity: 38-42 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 40	Multifleet SCD 30		
Change every 250 hours/ 1 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Change every 250 hours/ 1 months			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Change every 250 hours/ 1 months			
FINAL DRIVES Capacity: 60 liter (each side)			

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	

Check every 1 months/ 250 hours

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 1 months/ 250 hours	

USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Check every 1 months/ 250 hours	

CATERPILLAR TRACKED EXCAVATORS 245 94L (TILL 1990)



HYDRAULIC SYSTEM Capacity: 403 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 87 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	
Charle avery 4 manths/250 hours about	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

PUMP DRIVE Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 50 hours, change every 12 m	nths/ 2000 hours	

CATERPILLAR TRACKED EXCAVATORS 245 94L (TILL 1990)



SWING REDUCTION UNIT Capacity: 35 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 50	Multifleet SCD 40	
Check every 1 months/ 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 1 months/ 250 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 1 months/ 250 hours		

TRACK PINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRACK ROLLERS & IDLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.