

CATERPILLAR TRACKED EXCAVATORS

315C CFT (2000-2002)



ENGINE 3046
Capacity: 19 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 1 months/ 250 hours, change every 3 months/ 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Check every 1 months/ 250 hours, change every 3 months/ 500 hours

FINAL DRIVES

Capacity: 5 liter (each hub)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2
Gear Oil Alcat 50

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2
Gear Oil Alcat 50

Change every 250 hours

USE
Initial service

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Change every 250 hours

HYDRAULIC SYSTEM

Capacity: 121 liter

CATERPILLAR TRACKED EXCAVATORS

315C CFT (2000-2002)



| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 2000 hours/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra*Change every 2000 hours/ 12 months*

| USE | CLIMATE |
|--------------------|---------------|
| 50% use of breaker | Mediterranean |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 1000 hours*

| USE | CLIMATE |
|--------------------|----------|
| 50% use of breaker | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra*Change every 1000 hours*

| USE | CLIMATE |
|---------------------|---------------|
| 100% use of breaker | Mediterranean |

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 600 hours*

| USE | CLIMATE |
|---------------------|----------|
| 100% use of breaker | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra*Change every 600 hours*

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

CATERPILLAR TRACKED EXCAVATORS

315C CFT (2000-2002)



COOLING SYSTEM

Capacity: 1,5 liter (Reservoir), Capacity: 22 liter (System)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Extended drain (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Change every 6000 hours/ 72 months

SWING GEAR

Capacity: 17 liter

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 12 months/ 2000 hours

SWING REDUCTION UNIT

Capacity: 3 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Change every 250 hours

CATERPILLAR TRACKED EXCAVATORS

315C CFT (2000-2002)



TRACK IDLERS

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

TRACK ROLLERS

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 30 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.