

ENGINE C6.4 Acert Capacity: 30 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 500 hours/ 3 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	
Change every 500 hours/ 3 months		'

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours/ 1 months	5	
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		

HYDRAULIC SYSTEMCapacity: 138 liter (Total)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 2000 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra
Change every 2000 hours/ 12 months		
USE		CLIMATE
50% use of breaker		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Change every 1000 hours		
Change every 1000 hours USE		CLIMATE
USE		climate Moderate
use 50% use of breaker	PRODUCT RECOMMENDATION 2	
USE	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	Moderate
use 50% use of breaker PRODUCT RECOMMENDATION 1		Moderate PRODUCT RECOMMENDATION 3
use 50% use of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40		Moderate PRODUCT RECOMMENDATION 3
USE 50% use of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours		Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE		Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE
USE 50% use of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% use of breaker		Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% USE of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% USE of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% USE of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours		PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE Mediterranean
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% USE of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE		PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE Mediterranean CLIMATE
USE 50% USE of breaker PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 1000 hours USE 100% USE of breaker PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Change every 600 hours USE 100% USE of breaker	Agridiesel CRD+ 15W-40	Moderate PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra CLIMATE Mediterranean CLIMATE Moderate



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
USE	CLIMATE
Light Duty	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	
iii as ingii oraac orcasc	

COOLING SYSTEM Capacity: 25 liter, Capacity: 1,5 liter (Reservoir)		
USE	CLIMATE	
Extended drain (max)	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 12000 hours/ 72 months		

SWING GEAR Capacity: 22 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12 months/ 2000 hours



SWING REDUCTION UNIT Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		
TRACK IDLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
TRACK ROLLERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.