CATERPILLAR TRACKED EXCAVATORS 345B L 9GS (1997-1999)



Mediterranean PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
Multifleet SHPD 15W-40
CLIMATE
Moderate

FINAL DRIVES		
FINAL DRIVES Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	•
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		

HYDRAULIC SYSTEMCapacity: 370 liter (Refill)

CATERPILLAR TRACKED EXCAVATORS 345B L 9GS (1997-1999)



USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every	2000 hours/ 12 months	·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra
Check every 10 hours, change every	2000 hours/12 months	
use Up to 50% hammer use		climate Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every	/ 1000 hours/ 12 months	
USE		CLIMATE
Up to 50% hammer use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra
Check every 10 hours, change every	v 1000 hours/ 12 months	
USE		CLIMATE
Continuous hammer use		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every	600 hours/ 12 months	
Continuous hommer use		CLIMATE
Continuous hammer use		Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra
		Agrillulu Syntii Afir Oltia
Check every 10 hours, change every	v 600 hours/ 12 months	
GREASE POINTS/NIPPLES		
USE Normal		CLIMATE
Normal		Moderate

Moderate
meacrate
_

CATERPILLAR TRACKED EXCAVATORS 345B L 9GS (1997-1999)



COOLING SYSTEM Capacity: 73 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 m	nonths/ 6000 hours	
SWING GEAR Capacity: 41,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 2000 hours/ 12 months		
SWING REDUCTION UNIT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

Change every 250 hours

PRODUCT RECOMMENDATION

CATERPILLAR TRACKED EXCAVATORS 345B L 9GS (1997-1999)



information contained herein is subject to changes without notification.