## CATERPILLAR TRACKED EXCAVATORS 365C L (2005 AND AFTER)



Capacity: 54 liter		
USE		CLIMATE
Extended drain (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
USE		CLIMATE
Flexible (max)		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

## CATERPILLAR TRACKED EXCAVATORS 365C L (2005 AND AFTER)



USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiagal CRD : 15W 40	Agrifluid Synth XHP Ultra
RIGOTHIAK CV I 10VV-40	Agridiesel CRD+ 15W-40	Agrillulu Syntii AriF Olila
	Agridiesei CRD+ 13W-40	Agrillulu Syntii Arif Olula
GREASE POINTS/NIPPLES	Agridiesei CRD+ 13W-40	CLIMATE
GREASE POINTS/NIPPLES	Agridiesei CRD+ 13W-40	
GREASE POINTS/NIPPLES use Normal	Agridiesei CRD+ 13W-40	CLIMATE
GREASE POINTS/NIPPLES use Normal PRODUCT RECOMMENDATION 1 MoS2 Grease EP 2	Agridiesei CRD+ 13W-40	CLIMATE
GREASE POINTS/NIPPLES  use  Normal  PRODUCT RECOMMENDATION 1  MoS2 Grease EP 2	Agridiesei CRD+ 13W-40	CLIMATE Moderate
GREASE POINTS/NIPPLES  use  Normal  PRODUCT RECOMMENDATION 1	Agridiesei CRD+ 13W-40	CLIMATE

## CATERPILLAR TRACKED EXCAVATORS 365C L (2005 AND AFTER)



Change every 36 months/ 3000 hours		
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Acceptable		Moderate
USE		CLIMATE
Change every 24 months/ 3000 hours	\$	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE
Change every 12000 hours/72 month	ns	
Coolant SP 17		
PRODUCT RECOMMENDATION 1		
Extended drain (max)		Moderate
USE		CLIMATE
Change every 6000 hours/72 months	3	
Coolant SP 17		
PRODUCT RECOMMENDATION 1		
Extended		Moderate
USE		CLIMATE

SWING REDUCTION UNIT Capacity: 12 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
USE		CLIMATE
Flexible (max)		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

## CATERPILLAR TRACKED EXCAVATORS 365C L (2005 AND AFTER)



TRACK IDLERS	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRACK ROLLERS	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.