

CATERPILLAR TRACKED EXCAVATORS

6015FS DHF CUMMINS QSK19



ENGINE Cummins QSK19
Capacity: 66 liter (each engine)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 6 months/ 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---------------------------|-------------------------------------|--|
| Armado Synth 5W-30 | Dieselfleet LSP Ultra 10W-30 | |

Check every 10 hours, change every 6 months/ 250 hours

HYDRAULIC SYSTEM

Capacity: 1300 liter (Hydraulic tank), Capacity: 1700 liter (Total system volume)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 68 | | |

Check every 10 hours, change every 36 months/ 5000 hours

GREASE POINTS/NIPPLES AUTOMATIC LUBRICATION SYSTEM

Capacity: 10 kg

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| MoS2 Grease EP 2 | | |

Check every 10 hours

COOLING SYSTEM

Capacity: 115 liter (each engine)

| USE | CLIMATE |
|----------|----------|
| Extended | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Coolant SP 17 | | |

Check every 10 hours, change every 72 months/ 12000 hours

CATERPILLAR TRACKED EXCAVATORS

6015FS DHF CUMMINS QSK19



PUMP TRANSFER GEARBOX

Capacity: 13,5 liter (each (2x))

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

Check every 60 hours, change every 1000 hours

PUMP TRANSFER GEARBOX PRE-CHAMBERS (HYDRAULIC PUMPS)

Capacity: 0,2 liter

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

Check every 10 hours, change every 1000 hours

PUMP TRANSFER GEARBOX PRE-CHAMBERS (WORKING PUMPS)

Capacity: 1,4 liter (each (2x))

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

Check every 10 hours, change every 1000 hours

SWING DRIVE GEARBOX

Capacity: 26 liter (each (2x))

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 320 | | |

Check every 10 hours, change every 1000 hours

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

Check every 10 hours, change every 1000 hours

CATERPILLAR TRACKED EXCAVATORS

6015FS DHF CUMMINS QSK19

**TRAVEL REDUCTION GEARBOX P/N 3709660**

Capacity: 13,5 liter (each (2x))

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

*Check every 500 hours, change every 36 months/ 5000 hours***TRAVEL REDUCTION GEARBOX P/N 3712319**

Capacity: 18 liter (each (2x))

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

*Check every 500 hours, change every 36 months/ 5000 hours***TRAVEL REDUCTION GEARBOX P/N 3749594**

Capacity: 18 liter (each (2x))

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Abacot MEP Synth 220 | Abacot MEP 220 | |

Check every 500 hours, change every 36 months/ 5000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.