# **CATERPILLAR RIGID DUMP TRUCKS 771D**

(2001-2005)



| ENGINE 3408E<br>Capacity: 45 liter  |  |                                  |
|---|--|----------------------------------|
| USE   |  | CLIMATE                          |
| Extended drain (max)  |  | Mediterranean                    |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2                         | PRODUCT RECOMMENDATION 3         |
| Agridiesel CRD+ 15W-40  | Dieselfleet CD+ 15W-40                           | Multifleet SHPD 15W-40           |
| USE   |  | CLIMATE                          |
| Extended drain (max)  |  | Moderate                         |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2                         |                                  |
| Agrisynth LSP 10W-40  | Multifleet SHPD 10W-40                           |                                  |
|   |  |                                  |
| USE   |  | CLIMATE                          |
| use<br>Flexible (max)   |  | climate<br>Mediterranean         |
|   | PRODUCT RECOMMENDATION 2                         |                                  |
| Flexible (max)  | PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40 |                                  |
| Flexible (max) PRODUCT RECOMMENDATION 1   |  |                                  |
| Flexible (max)  PRODUCT RECOMMENDATION 1  Agridiesel CRD+ 15W-40  |  |                                  |
| Flexible (max)  PRODUCT RECOMMENDATION 1  Agridiesel CRD+ 15W-40  Change every 250 hours                      |  | Mediterranean                    |
| Flexible (max)  PRODUCT RECOMMENDATION 1  Agridiesel CRD+ 15W-40  Change every 250 hours  USE                 |  | Mediterranean                    |
| Flexible (max)  PRODUCT RECOMMENDATION 1  Agridiesel CRD+ 15W-40  Change every 250 hours  USE  Flexible (max) | Multifleet SHPD 15W-40                           | Mediterranean  CLIMATE  Moderate |

#### **DIFFERENTIAL REAR**

Capacity: 83 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### **FINAL DRIVES**

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR RIGID DUMP TRUCKS 771D




(2001-2005)

| USE                               |                | CLIMATE       |
|-----------------------------------|----------------|---------------|
| Normal                            |                | Mediterranean |
| PRODUCT RECOMMENDATION 1          |                |               |
| Gear Oil Alcat 30                 |                |               |
| Check every 500 hours, change eve | ery 1000 hours | ·             |
| USE                               |                | CLIMATE       |
| Normal                            |                | Moderate      |
| PRODUCT RECOMMENDATION 1          |                |               |
| Gear Oil Alcat 10W                |                |               |
| Check every 500 hours, change eve | ery 1000 hours |               |

| GREASE POINTS/NIPPLES    |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| MoS2 Grease EP 2         |          |
|                          |          |

### **CATERPILLAR RIGID DUMP TRUCKS 771D**





| USE                                |                          | CLIMATE                  |
|------------------------------------|--------------------------|--------------------------|
| Extended                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           |                          |                          |
| Coolant SP 17                      |                          |                          |
| Change every 6000 hours/ 72 months |                          | ·                        |
| USE                                |                          | CLIMATE                  |
| Extended drain (max)               |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           |                          |                          |
| Coolant SP 17                      |                          |                          |
| Change every 12000 hours/72 months | }                        |                          |
| USE                                |                          | CLIMATE                  |
| Alternative (acceptable)           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                     | Coolant SP 12            | Coolant -38 Organic NF   |
| Change every 24 months/ 3000 hours |                          |                          |
| USE                                |                          | CLIMATE                  |
| Acceptable                         |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| PRODUCT RECOMMENDATION I           |                          |                          |

| BRAKE/HOIST SYSTEM Capacity: 277 liter (Complete), Capacity: 133 liter (Hydraulic tank) |  |  |  |
|---|--|--|--|
| CLIMATE   |  |  |  |
| Moderate  |  |  |  |
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |

| POWER STEERING HYDRAULIC SYSTEM Capacity: 56 liter (Complete), Capacity: 34 liter (Hydraulic tank) |                          |                          |  |
|--|--------------------------|--------------------------|--|
| USE  |                          | CLIMATE                  |  |
| Normal   |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |
| Agridiesel CRD+ 15W-40   | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |  |

PRODUCT RECOMMENDATION

# CATERPILLAR RIGID DUMP TRUCKS 771D



(2001-2005)

| SUSPENSION CYLINDERS     |  |          |  |
|--------------------------|--|----------|--|
| USE                      |  | CLIMATE  |  |
| Normal                   |  | Moderate |  |
| PRODUCT RECOMMENDATION 1 |  |          |  |
| Multifleet SCD 10W       |  |          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.