## CATERPILLAR WHEELED LOADERS 914G CATERPILLAR 3054 T (1995-2005)



ENGINE 3054T Capacity: 7 liter		
USE		CLIMATE
Extended drain (max)		Mediterranean
	PROPURT RECOMMENDATION O	
PRODUCT RECOMMENDATION 1  Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2  Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 3  Multifleet SHPD 15W-40
	Diesemeet OD+ 1317 40	Material D 10W 40
Change every 500 hours		
USE Extended drain (max)		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
Change every 500 hours		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Change every 250 hours		·
DIFFERENTIAL FRONT		
Capacity: 15 liter		
USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
USE		CLIMATE
Flexible (max)		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Joan On Albat 1011		

## CATERPILLAR WHEELED LOADERS 914G CATERPILLAR 3054 T (1995-2005)



DIFFERENTIAL REAR Capacity: 15 liter	
USE	CLIMATE
Flexible (max)	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
USE	CLIMATE
Flexible (max)	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

use Flexible (max)		climate Moderate
Helar 0W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30
ISE STATE OF THE S		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

use Flexible (max)		сымате Mediterranean
Multifleet SCD 30	Gear Oil Alcat 30	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
lelar 0W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

## CATERPILLAR WHEELED LOADERS 914G CATERPILLAR 3054 T (1995-2005)



## **FAN DRIVE BEARINGS**

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
USE		CLIMATE
Light Duty		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		
COOLING SYSTEM		
Capacity: 23 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 6000 hours/ 72 months		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Change every 12000 hours/ 72 months		1
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 36 months/ 3000 hours	-	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Coolant SP 12

Coolant SP 15+

Change every 24 months/ 3000 hours

Coolant -38 Organic NF