## JCB HIGH MOBILITY VEHICLES FASTRAC 110



ENGINE Perkins 1006.6		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Mediterranean
	PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40	Mediterranean
PRODUCT RECOMMENDATION 1		Mediterranean
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40		CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours		
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1		CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service		CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1		CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SHPD 10W-40  Change every 100 hours  USE		CLIMATE  CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SHPD 10W-40  Change every 100 hours		CLIMATE Moderate
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SHPD 10W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1		CLIMATE  CLIMATE
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40  Change every 100 hours  USE Initial service  PRODUCT RECOMMENDATION 1  Multifleet SHPD 10W-40  Change every 100 hours  USE Initial service		CLIMATE  CLIMATE

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
Change every 1000 hours/ 12 mont	hs	·

## JCB HIGH MOBILITY VEHICLES FASTRAC 110



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
Change avery 1000 hours/12 man	tho	'

Change every 1000 hours/ 12 months

TRANSFERBOX/P.T.O. FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours/ 12 month	hs	

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 2000 hours/ 24 months	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## JCB HIGH MOBILITY VEHICLES FASTRAC 110



POWER TAKE OFF SPEED + RANGE GEARBOXES (COMBINED) -> 63001		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Agrifluid HT	
Change every 1000 hours/12 months		

Change every 1000 hours/ 12 months

information contained herein is subject to changes without notification.

POWER TAKE OFF SPEED + RANGE GEARBOXES (COMBINED) 63001 ->		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 1000 hours/ 12 months		

SPEED GEARBOX -> 636001		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours/ 12 mont	hs	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V. Postbus 149 7600 AC Almelo