

JCB HIGH MOBILITY VEHICLES FASTRAC 145 TURBO


ENGINE Perkins 1006.6T

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Multifleet SHPD 10W-40 | | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 100 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Multifleet SHPD 10W-40 | | |

Change every 100 hours

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Change every 100 hours

DIFFERENTIAL FRONT

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|------------------------------------|
| Agrifluid HT | Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |

Change every 1000 hours/ 12 months

JCB HIGH MOBILITY VEHICLES FASTRAC 145 TURBO



DIFFERENTIAL REAR

| USE | | CLIMATE |
|--|-----------------------------|------------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT | Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |
| <i>Change every 1 months/ 1000 hours</i> | | |

HUB REDUCTIONS FRONT

| USE | | CLIMATE |
|---|-----------------------------|------------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT | Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 |
| <i>Change every 1000 hours/ 12 months</i> | | |

TRANSFERBOX/P.T.O. FRONT

| USE | | CLIMATE |
|---|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| <i>Change every 1000 hours/ 12 months</i> | | |

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|---|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |
| <i>Change every 2000 hours/ 24 months</i> | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

JCB HIGH MOBILITY VEHICLES FASTRAC 145 TURBO


POWER TAKE OFF SPEED + RANGE GEARBOXES (COMBINED) -> 63001

| USE | | CLIMATE |
|-----------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Kroontrak MTH 10W-30 | Agrifluid HT | |

Change every 1000 hours/ 12 months

POWER TAKE OFF SPEED + RANGE GEARBOXES (COMBINED) 63001 ->

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |

Change every 1000 hours/ 12 months

SPEED GEARBOX -> 636001

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.