JCB TELESCOPIC HANDLERS 926



USE		
		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

DIFFERENTIAL FRONT Capacity: 29,5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

DIFFERENTIAL REAR Capacity: 15 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HUB REDUCTIONS REAR Capacity: 1,3 liter (each hub)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

JCB TELESCOPIC HANDLERS 926



TRANSMISSION SynchroShuttle Capacity: 17,3-18,3 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	

HYDRAULIC SYSTEM Capacity: 64 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 32	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Perlus H 15	

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

GREASE POINTS/NIPPLES TELESCOPIC SLIDING SURFACES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 17 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.