

JCB WHEELED LOADERS 416 529000- >1242999 (1994-1997)



ENGINE Perkins 1000T
Capacity: 10,7 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1
Multifleet SCD 10W

Check every 10 hours, change every 500 hours/ 6 months

DIFFERENTIAL FRONT
Capacity: 25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Change every 100 hours

DIFFERENTIAL REAR
Capacity: 25 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Check every 6 months/ 500 hours, change every 12 months/ 1000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Change every 100 hours

JCB WHEELED LOADERS 416 529000- >1242999 (1994-1997)

**TRANSMISSION**

Capacity: 19 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Check every 50 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 125 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32*Check every 10 hours, change every 1000 hours/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 15*Check every 10 hours, change every 1000 hours/ 12 months***GREASE POINTS/NIPPLES**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease**COOLING SYSTEM**

Capacity: 26 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Check every 6 months/ 500 hours, change every 24 months/ 2000 hours*

JCB WHEELED LOADERS 416 529000- >1242999 (1994-1997)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.