PRODUCT RECOMMENDATION

# JCB WHEELED LOADERS 416 HT JCB 444
(2007-2013)

**ENGINE** JCB 444
Capacity: 11,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel MSP 15W-40** | **Agridiesel CRD+ 15W-40** | **Dieselfleet CD+ 15W-40** |

**DIFFERENTIAL FRONT** JCB PD87
Capacity: 25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Agrifluid HT-Plus** | **Agrifluid HT** |

**DIFFERENTIAL FRONT** JCB PD90
Capacity: 25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Agrifluid HT-Plus** | **Agrifluid HT** |

**DIFFERENTIAL REAR** JCB PD87
Capacity: 25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Agrifluid HT-Plus** | **Agrifluid HT** |

**DIFFERENTIAL REAR** JCB PD90
Capacity: 25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Agrifluid HT-Plus** | **Agrifluid HT** |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# JCB WHEELED LOADERS 416 HT JCB 444
(2007-2013)

## TRANSMISSION ZF 4WG115 4/3
Capacity: 27 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **SP Matic 2032** | | |

## HYDRAULIC SYSTEM
Capacity: 125 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Perlus H 32** | | |

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **HT Q9 High Grade Grease** | | |

## COOLING SYSTEM
Capacity: 23 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367