JCB WHEELED LOADERS 416S STAGE IIIA/T3 (1243500->1243999) (2007 AND



AFTER)

ENGINE JCB Dieselmax Tier 3 USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

HUB REDUCTIONS FRONT	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

HUB REDUCTIONS REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

TRANSMISSION		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
		<u>'</u>

JCB WHEELED LOADERS 416S STAGE IIIA/T3 (1243500->1243999) (2007 AND



AFTER)

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HT Q9 High Grade Grease	Labora Grease		

GREASE POINTS/NIPPLES CENTRAL LUBRICATION SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.