## KUBOTA TRACKED EXCAVATORS K/KH/KX/U KH91 KUBOTA D1402-BH (1987-1991)



ENGINE Kubota D1402 Capacity: 4 liter		
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Change every 100 hours		-
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	
Change every 100 hours		
use Normal		climate Cold
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40
Change every 100 hours	1	1
use Initial service		climate Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Change every 35 hours		
use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40	
Change every 35 hours		
use Initial service		climate Cold
PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 10W-40

Change every 35 hours

## KUBOTA TRACKED EXCAVATORS K/KH/KX/U KH91 KUBOTA D1402-BH (1987-1991)



HYDRAULIC SYSTEM Capacity: 85 liter (Hydraulic tank), Capacit	y: 110 liter (Total system volume)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 1000 hours		-
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Change every 1000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 1000 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SWING BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SWING GEAR TEETH		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## KUBOTA TRACKED EXCAVATORS K/KH/KX/U KH91 KUBOTA D1402-BH (1987-1991)



SWING REDUCTION UNIT Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

TRAVEL REDUCTION UNIT Capacity: 2,3 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.