

PRODUCT RECOMMENDATION

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX61-3 KUBOTA V1505-E2-BH

### (2004 AND AFTER)



**ENGINE** Kubota V1505-E2B  
Capacity: 5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 50**

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 250 hours/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

*Check every 10 hours, change every 250 hours/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 50**

*Change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

PRODUCT RECOMMENDATION 3

**Dieselfleet CD+ 15W-40**

*Change every 50 hours*

| USE             | CLIMATE |
|-----------------|---------|
| Initial service | Cold    |

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

*Change every 50 hours*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX61-3 KUBOTA V1505-E2-BH

### (2004 AND AFTER)



| USE                          |  | CLIMATE |
|------------------------------|--|---------|
| Initial service              |  | Arctic  |
| PRODUCT RECOMMENDATION 1     |  |         |
| <b>Multifleet SCD 10W</b>    |  |         |
| <i>Change every 50 hours</i> |  |         |

| HYDRAULIC SYSTEM  |                          |                          |
|---|--------------------------|--------------------------|
| Capacity: 53 liter (Hydraulic system including tank), Capacity: 38 liter (Hydraulic tank) |                          |                          |
| USE   |                          | CLIMATE                  |
| Breaker use 40 - 60%  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |
| <i>Check every 10 hours, change every 400 hours</i>                                       |                          |                          |

| USE   |                          | CLIMATE |
|---|--------------------------|---------|
| Breaker use 40 - 60%                                |                          | Cold    |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 32</b>                                  | <b>Perlus AF 32</b>      |         |
| <i>Check every 10 hours, change every 400 hours</i> |                          |         |

| USE   |                          | CLIMATE                  |
|---|--------------------------|--------------------------|
| Breaker use 60 - 80%                                |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>                                  | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |
| <i>Check every 10 hours, change every 300 hours</i> |                          |                          |

| USE   |                          | CLIMATE |
|---|--------------------------|---------|
| Breaker use 60 - 80%                                |                          | Cold    |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 32</b>                                  | <b>Perlus AF 32</b>      |         |
| <i>Check every 10 hours, change every 300 hours</i> |                          |         |

| USE   |                          | CLIMATE                  |
|---|--------------------------|--------------------------|
| Breaker use > 80%                                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>                                  | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |
| <i>Check every 10 hours, change every 200 hours</i> |                          |                          |

| USE   |                          | CLIMATE |
|---|--------------------------|---------|
| Breaker use > 80%                                   |                          | Cold    |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 32</b>                                  | <b>Perlus AF 32</b>      |         |
| <i>Check every 10 hours, change every 200 hours</i> |                          |         |

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX61-3 KUBOTA V1505-E2-BH

### (2004 AND AFTER)



| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Breaker use < 20%        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |

*Check every 10 hours, change every 1000 hours*

| USE                      |                          | CLIMATE |
|--------------------------|--------------------------|---------|
| Breaker use < 20%        |                          | Cold    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 32</b>       | <b>Perlus AF 32</b>      |         |

*Check every 10 hours, change every 1000 hours*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Breaker use 20 - 40%     |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Perlus H 46</b>       | <b>Perlus H 68</b>       | <b>Perlus AF 46</b>      |

*Check every 10 hours, change every 800 hours*

| USE                      |                          | CLIMATE |
|--------------------------|--------------------------|---------|
| Breaker use 20 - 40%     |                          | Cold    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |         |
| <b>Perlus H 32</b>       | <b>Perlus AF 32</b>      |         |

*Check every 10 hours, change every 800 hours*

#### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

#### COOLING SYSTEM

Capacity: 5,4 liter, Capacity: 1,1 liter (Reserve tank)

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 10 hours, change every 24 months*

# KUBOTA TRACKED EXCAVATORS

## K/KH/KX/U KX61-3 KUBOTA V1505-E2-BH

### (2004 AND AFTER)

**TRAVEL REDUCTION UNIT**

Capacity: 0,6 liter (each)

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Moderate                     |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

*Change every 500 hours*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Cold                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1081</b>      | <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |

*Change every 500 hours*

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Initial service             |                                    | Moderate                     |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

*Change every 100 hours*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Initial service          |                          | Cold                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1081</b>      | <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |

*Change every 100 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.