PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U35-3A3 KUBOTA D1803-M-E3B (2011 AND AFTER)

ENGINE Kubota D1803-M-E3B
Capacity: 6,6 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 40**

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Check every 10 hours, change every 500 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 500 hours

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 50		

Change every 50 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 40**

Change every 50 hours

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U35-3A3 KUBOTA D1803-M-E3B (2011 AND AFTER)

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 33 liter (Hydraulic tank), Capacity: 41 liter (System)

USE	CLIMATE
Breaker use 40 - 60%	Tropical

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 400 hours

USE	CLIMATE
Breaker use 40 - 60%	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 400 hours

USE	CLIMATE
Breaker use 40 - 60%	Cold

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 10 hours, change every 400 hours

USE	CLIMATE
Breaker use 60 - 80%	Tropical

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 10 hours, change every 300 hours

USE	CLIMATE
Breaker use 60 - 80%	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 300 hours

USE	CLIMATE
Breaker use 60 - 80%	Cold

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 10 hours, change every 300 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U35-3A3 KUBOTA D1803-M-E3B (2011 AND AFTER)

USE	CLIMATE
Breaker use > 80%	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 68	

Check every 10 hours, change every 200 hours

USE	CLIMATE
Breaker use > 80%	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

Check every 10 hours, change every 200 hours

USE	CLIMATE
Breaker use > 80%	Cold
PRODUCT RECOMMENDATION 1	
Perlus H 32	

Check every 10 hours, change every 200 hours

USE	CLIMATE
Breaker use < 20%	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 68	

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Breaker use < 20%	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Breaker use < 20%	Cold
PRODUCT RECOMMENDATION 1	
Perlus H 32	

Check every 10 hours, change every 1000 hours

USE	CLIMATE
Breaker use 20 - 40%	Tropical
PRODUCT RECOMMENDATION 1	
Perlus H 68	

Check every 10 hours, change every 800 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U35-3A3 KUBOTA D1803-M-E3B (2011 AND AFTER)

USE		CLIMATE
Breaker use 20 - 40%		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 800 hours

USE		CLIMATE
Breaker use 20 - 40%		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 10 hours, change every 800 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

COOLING SYSTEM
Capacity: 5,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Change every 24 months

TRAVEL REDUCTION UNIT
Capacity: 0,6 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA TRACKED EXCAVATORS K/KH/KX/U U35-3A3 KUBOTA D1803-M-E3B (2011 AND AFTER)

information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367