MANITOU MANITRANSIT RANGE TMD/TME/TMP/TMT/TMV TMP 55 PERKINS 404C--22 TIER 2 (751864 ->)



PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30

ENGINE Perkins 404C-22 Capacity: 5,6 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change every	y 200 hours	·
USE		CLIMATE
Normal		Moderate

Check every 10 hours, change every 200 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Armado Synth 5W-30

Change every 50 hours

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Synfleet SHPD 10W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30	
Change every 50 hours			

HYDRAULIC SYSTEM Capacity: 40 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Perlus H 46			
01 1 501	0001 / 10 /1	<u> </u>	

Check every 50 hours, change every 800 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

PRODUCT RECOMMENDATION

MANITOU MANITRANSIT RANGE TMD/TME/TMP/TMT/TMV TMP 55 PERKINS 404C--22 TIER 2 (751864 ->)



GREASE POINTS/NIPPLES MAST CARRIER THRUST PADS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 10 hours		

COOLING SYSTEM Capacity: 8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 10 hours, change every 800 hours/ 12 month	hs .

MAST CHAINS

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.