

# MANITOU MANITRANSIT RANGE

## TMD/TME/TMP/TMT/TMV TMP 5500 HT

### LISTER PETTER LPW-S4 (165126 - 751863)



**ENGINE** Lister Petter LPW S4  
Capacity: 5,6 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Check every 10 hours, change every 200 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3   |
|-----------------------------|-----------------------------|----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Armado Synth 10W-40</b> |

*Check every 10 hours, change every 200 hours*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

*Change every 50 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3   |
|-----------------------------|-----------------------------|----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Armado Synth 10W-40</b> |

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 40 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 46</b>       |  |  |

*Check every 50 hours, change every 800 hours/ 12 months*

#### GREASE POINTS/NIPPLES GENERAL

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2       |  |
|---------------------------------|--------------------------------|--|
| <b>Q7 MP Calcep Grease WR 2</b> | <b>Caliplex HD Grease EP 2</b> |  |

# MANITOU MANITRANSIT RANGE

## TMD/TME/TMP/TMT/TMV TMP 5500 HT

### LISTER PETTER LPW-S4 (165126 - 751863)



#### GREASE POINTS/NIPPLES MAST CARRIER THRUST PADS

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Change every 10 hours*

#### COOLING SYSTEM

Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 10 hours, change every 800 hours/ 12 months*

#### MAST CHAINS

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*