PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

Check every 400 hours, change every 1600 hours

## **FIAT-TRATTORI 80 580, 580 DT** (1978-1984)



| <b>ENGINE</b> 8035.04 Capacity: 7,4 liter, Filter capacity: 0,6 liter |               |  |
|---|---------------|--|
| USE   | CLIMATE       |  |
| Normal  | Mediterranean |  |
| PRODUCT RECOMMENDATION 1  |               |  |
| Kroontrak CVT 10W-40  |               |  |
| Change every 200 hours  |               |  |
| USE   | CLIMATE       |  |
| Normal  | Moderate      |  |
| PRODUCT RECOMMENDATION 1  |               |  |
| Kroontrak MTH 10W-30  |               |  |
| Change every 200 hours  |               |  |
|   |               |  |
| <b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 4,6 liter                   |               |  |
| USE   | CLIMATE       |  |
| Normal  | Moderate      |  |

| HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Kroontrak CVT 10W-40                           |          |
| Check every 400 hours, change every 1600 hours | '        |

| TRANSMISSION MANUAL 8/2 Capacity: 10 liter     |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Kroontrak CVT 10W-40                           |          |
| Check every 400 hours, change every 1600 hours | '        |

## **FIAT-TRATTORI 80 580, 580 DT** (1978-1984)



| HYDRAULIC SYSTEM/REAR AXL Capacity: 44,5 liter | E                        |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |          |
| Agrifluid HT-Plus                              | Agrifluid HT             |          |
| Check every 400 hours, change every 1600 hours |                          |          |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal                                     | Moderate |
| PRODUCT RECOMMENDATION 1                   |          |
| Multifleet SCD 10W                         |          |

| POWER STEERING<br>Capacity: 1,7 liter |               |
|---------------------------------------|---------------|
| USE                                   | CLIMATE       |
| Normal                                | Mediterranean |
| PRODUCT RECOMMENDATION 1              |               |
| Kroontrak CVT 10W-40                  |               |
| Change every 800 hours                |               |
| USE                                   | CLIMATE       |
| Normal                                | Moderate      |
| PRODUCT RECOMMENDATION 1              |               |
| Kroontrak MTH 10W-30                  |               |
| Change every 800 hours                |               |

| GREASE POINTS/NIPPLES OTHERS |                          |          |  |
|------------------------------|--------------------------|----------|--|
| USE                          |                          | CLIMATE  |  |
| Normal                       |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 |          |  |
| Q7 MP Calcep Grease WR 2     | Caliplex HD Grease EP 2  |          |  |
| Check every 50 hours         | 1                        |          |  |

## FIAT-TRATTORI 80 580, 580 DT (1978-1984)



| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal                                     |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |  |
| Q7 MP Calcep Grease WR 2                   | Caliplex HD Grease EP 2  |          |  |
| Chock ayon, 400 hours                      | 1                        | '        |  |

Check every 400 hours

| COOLING SYSTEM Capacity: 10-13 liter |                          |          |  |
|--------------------------------------|--------------------------|----------|--|
| USE                                  |                          | CLIMATE  |  |
| Normal                               |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant -38 Organic NF               | Coolant -26              |          |  |
| Change every 1600 hours              | '                        | '        |  |

| BELT PULLEY Capacity: 1,1 liter       |          |          |
|---------------------------------------|----------|----------|
| USE                                   |          | CLIMATE  |
| Normal                                |          | Moderate |
| PRODUCT RECOMMENDATION 1              |          |          |
| Kroontrak CVT 10W-40                  |          |          |
| Check every 50 hours, change every 10 | 00 hours |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.