

RENAULT 100 681, 681-4 (1980-1987)**ENGINE** MWM D 227-4

Capacity: 10,3 liter, Filter capacity: 0,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT PR 721

Capacity: 3,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT PA 721

Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE/HYDRAULIC SYSTEM 12/3

Capacity: 44 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES OTHERS**USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 2****MP Lithep Grease EP 2**

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 2****MP Lithep Grease EP 2**

Check every 200 hours

COOLING SYSTEM

Capacity: 12,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 16**

Check every 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.