

ACURA (USA / CAN) TL UA6, UA7 TL 3.2 (2004-2005)

**ENGINE J32A3**

Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill)

USE

Flexible (on board maintenance system)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20****TRANSAXLE AUTOMATIC 5/1**

Capacity: 7,2 liter (Dry fill), Capacity: 2,9 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026****TRANSAXLE MANUAL 6/1**

Capacity: 2,5 liter (Dry fill), Capacity: 2,2 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015****HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3***Check every 1 months, change every 36 months***HYDRAULIC CLUTCH SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3***Check every 1 months, change every 36 months***POWER STEERING**

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) TL UA6, UA7 TL 3.2 (2004-2005)

**COOLING SYSTEM**

Capacity: 7,9-8,1 liter (Dry fill), Capacity: 6,3-6,4 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.