ALFA ROMEO (EU) 146 930 146 1.7 16V (1995-1997)



ENGINE Capacity: 4,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Emperol Racing 10W-60	Emperol 10W-40		
Check every 500 km, change every 20000 km/ 12 months			
USE		CLIMATE	
Normal		Arctic	

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2
Asyntho 5W-30

Check every 500 km, change every 20000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 2,6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		
Check every 40000 km, change every 120000 km		

HYDRAULIC BRAKE/CLUTCH SYSTEM
USE CLIMATE

Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE

Check every 500 km, change every 12 months

POWER STEERING Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 500 km	

ALFA ROMEO (EU) 146 930 146 1.7 16V (1995-1997)



COOLING SYSTEM Capacity: 7,8 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 500 km, change every 60000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.