## ALFA ROMEO (EU) 155 167 155 1.8 T.SPARK 16V (1996-1997)



ENGINE Capacity: 4,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Emperol Racing 10W-60	Emperol 10W-40		
Check every 500 km, change every 20000 km/ 12 months			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Duranza LSP 5W-30	Asyntho 5W-30		

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 80000 km/ 48 months		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,55 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 500 km, change every 60000 km/24 months

Check every 500 km, change every 20000 km/ 12 months

POWER STEERING Capacity: 1,43 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 500 km	

## **ALFA ROMEO (EU) 155 167 155 1.8** T.SPARK 16V (1996-1997)



COOLING SYSTEM Capacity: 8,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 500 km, change every 60000 km/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.