

ALFA ROMEO (EU) 75 162B 75 2.0 (1985-1988)



ENGINE

Capacity: 5,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

HDX 20W-50*Change every 10000 km/ 6 months*

TRANSAXLE MANUAL 5/1

Capacity: 2,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90*Check every 20000 km, change every 40000 km/ 24 months*

HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 12 months*

HYDRAULIC CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Change every 40000 km/ 12 months*

ALFA ROMEO (EU) 75 162B 75 2.0 (1985-1988)**COOLING SYSTEM**

Capacity: 8,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 40000 km/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.