

# AUDI (EU) A1, S1 8X A1 1.0 TFSI (60 KW) (2015-2018)

**ENGINE CHZE**

Capacity: 4 liter (Service fill)

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

## PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

Change every 30000 km/ 24 months

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Helar 0W-40**

## PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 3

**Asyntho 5W-30**

Change every 15000 km/ 12 months

**TRANSAXLE MANUAL 0DF 5/1**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 1081**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

Check every 24 months/ 30000 km

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

Change every 30000 km/ 24 months

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO**

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.