

PRODUCT RECOMMENDATION

# AUDI (EU) A4, S4, RS 4 8K A4 2.0 TFSI (132 KW) (2008-2012)



**ENGINE** CAEA, CDNB  
Capacity: 4,6 liter (Service fill)

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Change every 30000 km/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Helar 0W-40**

PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

PRODUCT RECOMMENDATION 3

**Asyntho 5W-30**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Change every 15000 km/ 12 months*

**DIFFERENTIAL CVT**  
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1071**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*

**TRANSAXLE MANUAL** 0B1 6/1  
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!  
Check every 24 months/ 30000 km*

# AUDI (EU) A4, S4, RS 4 8K A4 2.0 TFSI (132 KW) (2008-2012)



**TRANSMISSION CVT 0AW 1/1**  
Capacity: 8 liter (Dry fill), Capacity: 5,5-6 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4016</b>		

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
Change every 60000 km

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-LV Super DOT 4</b>		

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
Change every 24 months

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
Check every 24 months/ 30000 km

## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

*Vehicles with extended drain intervals can be identified by the presence of the code QG1 on the vehicle identification plate. If this code is not present (or mentions code QG0 or QG2) only the normal drain intervals may be used!*  
Check every 24 months/ 30000 km

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*