PRODUCT RECOMMENDATION

AUDI (EU) A6, S6, RS 6 4F A6 2.0 TDI (103 KW) (2005-2008)

ENGINE BLB
Capacity: 3,8 liter

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Helar SP LL-03 0W-30	**Helar SP LL-03 5W-30**	
Change every 30000 km/ 24 months		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Helar SP LL-03 5W-30	**Presteza MSP 5W-30**	**Specialsynth MSP 5W-40**
Change every 15000 km/ 12 months		

DIFFERENTIAL CVT
Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
Check every 60000 km/ 36 months		

TRANSAXLE CVT 01J 1/1
Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4016		
Change every 60000 km		

TRANSAXLE MANUAL 01X 6/1
Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Gear 1011	**Syngear TDL 75W-90**	
Check every 30000 km		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AUDI (EU) A6, S6, RS 6 4F A6 2.0 TDI (103 KW) (2005-2008)

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12++	**Coolant SP 12 EVO**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367