

MAN TGL EURO 3/4 TGL 8.180 BB/BL (4X2)

EURO 4 (2006-2011)



ENGINE D 0834 LFL51/54/Euro 4
Capacity: 16,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40
<i>Change every 80000 km/ 12 months</i>		

DIFFERENTIAL REAR MAN HY-0718
Capacity: 5,25 liter

USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 300000 km/ 36 months</i>		

USE		CLIMATE
Extended, tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 24 months</i>		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
<i>Change every 125000 km/ 24 months</i>		

USE		CLIMATE
Tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 130000 km/ 24 months</i>		

MAN TGL EURO 3/4 TGL 8.180 BB/BL (4X2) EURO 4 (2006-2011)



USE		CLIMATE
Alternative (acceptable), tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
<i>Change every 80000 km/ 24 months</i>		

TRANSMISSION MANUAL ZF 6S-850 6/1 Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 240000 km/ 24 months</i>		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90
<i>Change every 120000 km/ 12 months</i>		

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH + HGS (KONGSBERG) GEAR ACTUATION SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		



MAN TGL EURO 3/4 TGL 8.180 BB/BL (4X2)

EURO 4 (2006-2011)



POWER STEERING ZF 8095

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

CENTRAL LUBRICATION SYSTEM BEKA-MAX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

CENTRAL LUBRICATION SYSTEM Groeneveld

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

CENTRAL LUBRICATION SYSTEM GREASE Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

CENTRAL LUBRICATION SYSTEM OIL Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 10W-40	Armado Synth 5W-30	

MAN TGL EURO 3/4 TGL 8.180 BB/BL (4X2)

EURO 4 (2006-2011)



GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.