

# MAN TGX EURO 4 TGX 26.360 (6X2/2) SCR EURO 4 (2008 AND AFTER)



**ENGINE** D 2066 LF64/71 SCR  
Capacity: 42 liter

| USE           | CLIMATE  |
|---------------|----------|
| Long distance | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2             | PRODUCT RECOMMENDATION 3       |
|-------------------------------------|--------------------------------------|--------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |

*Change every 90000 km/ 12 months*

| USE                                                        | CLIMATE  |
|------------------------------------------------------------|----------|
| Regional, fuel < 30 L/100 km, fuel sulfur content < 50 ppm | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2             | PRODUCT RECOMMENDATION 3       |
|-------------------------------------|--------------------------------------|--------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |

*Change every 70000 km/ 12 months*

| USE                                                             | CLIMATE  |
|-----------------------------------------------------------------|----------|
| Distribution, fuel 30-50 L/100 km, fuel sulfur content < 50 ppm | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2             | PRODUCT RECOMMENDATION 3       |
|-------------------------------------|--------------------------------------|--------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |

*Change every 50000 km/ 12 months*

| USE                                                     | CLIMATE  |
|---------------------------------------------------------|----------|
| Severe, fuel >50 L/100 km, fuel sulfur content < 50 ppm | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2             | PRODUCT RECOMMENDATION 3       |
|-------------------------------------|--------------------------------------|--------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |

*Change every 30000 km/ 12 months*

**DIFFERENTIAL REAR** HY-1350  
Capacity: 14,5 liter

| USE      | CLIMATE  |
|----------|----------|
| Extended | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |  |
|--------------------------|---------------------------|--|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |  |

*Change every 500000 km/ 36 months*

| USE                        | CLIMATE  |
|----------------------------|----------|
| Extended, tropical climate | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |  |
|--------------------------|---------------------------|--|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |  |

*Change every 360000 km/ 36 months*

# MAN TGX EURO 4 TGX 26.360 (6X2/2) SCR EURO 4 (2008 AND AFTER)



| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

*Change every 320000 km/ 24 months*

| USE                      |                           | CLIMATE                     |
|--------------------------|---------------------------|-----------------------------|
| Alternative (acceptable) |                           | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3    |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Gearlube GL-5 80W-90</b> |

*Change every 160000 km/ 24 months*

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Tropical climate         |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

*Change every 210000 km/ 24 months*

| USE                                        |                           | CLIMATE                     |
|--------------------------------------------|---------------------------|-----------------------------|
| Alternative (acceptable), tropical climate |                           | Moderate                    |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3    |
| <b>SP Gear 1011</b>                        | <b>Syngear TDL 75W-90</b> | <b>Gearlube GL-5 80W-90</b> |

*Change every 110000 km/ 24 months*

## TRANSMISSION AUTOMATIC ZF 12AS-2130 DD (TipMatic) 12/1 Capacity: 12 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Syngear MT/LD 75W-80</b> |  |          |

*Change every 320000 km/ 24 months*

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Alternative (acceptable) |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear HS 75W-90</b> |

*Change every 160000 km/ 12 months*

# MAN TGX EURO 4 TGX 26.360 (6X2/2) SCR EURO 4 (2008 AND AFTER)


**TRANSMISSION MANUAL ZF 16S-2220 16/2**

Capacity: 13 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Syngear MT/LD 75W-80***Change every 320000 km/ 24 months*

| USE                      | CLIMATE  |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear HS 75W-90***Change every 160000 km/ 12 months*
**HYDRAULIC CAB TILT SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 15**
**HYDRAULIC CLUTCH + HGS (KONGSBERG) GEAR ACTUATION SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**
**HYDRAULIC CLUTCH SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

# MAN TGX EURO 4 TGX 26.360 (6X2/2) SCR EURO 4 (2008 AND AFTER)



## POWER STEERING ZF 8098

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Alternative (acceptable) |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

## CENTRAL LUBRICATION SYSTEM BEKA-MAX

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>HT Q9 High Grade Grease</b> |  |          |

## CENTRAL LUBRICATION SYSTEM Groeneveld

| USE                      |                              | CLIMATE  |
|--------------------------|------------------------------|----------|
| Normal                   |                              | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2     |          |
| <b>Gear Grease EP 0</b>  | <b>Gear Grease EP 00/000</b> |          |

## CENTRAL LUBRICATION SYSTEM GREASE Vogel

| USE                          |  | CLIMATE  |
|------------------------------|--|----------|
| Normal                       |  | Moderate |
| PRODUCT RECOMMENDATION 1     |  |          |
| <b>Gear Grease EP 00/000</b> |  |          |

## CENTRAL LUBRICATION SYSTEM OIL Vogel

| USE                                  |                                | CLIMATE  |
|--------------------------------------|--------------------------------|----------|
| Normal                               |                                | Moderate |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2       |          |
| <b>Armado Synth LSP Ultra 10W-40</b> | <b>Armado Synth LSP 10W-40</b> |          |

# MAN TGX EURO 4 TGX 26.360 (6X2/2) SCR EURO 4 (2008 AND AFTER)



## WHEEL BEARINGS REAR

Capacity: 120 grams (each side)

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>HT Q9 High Grade Grease</b> |  |          |

## COOLING SYSTEM

Capacity: 52 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.