

ALFA ROMEO (EU) 164 164 164 2.0 V6 TURBO (1991-1994)



MOTOR 64102
Kapasitet: 7 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Emperol Racing 10W-60

PRODUKTANBEFALING 2
Emperol 10W-40

Sjekk hver 500 km, bytt hver 10000 km/ 12 måneder

BRUK
Normal

KLIMA
Arktis

PRODUKTANBEFALING 1
Duranza LSP 5W-30

PRODUKTANBEFALING 2
Asyntho 5W-30

Sjekk hver 500 km, bytt hver 10000 km/ 12 måneder

TRANSAKSEL MANUELL 5/1
Kapasitet: 1,8 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Gearlube GL-4 80W

Sjekk hver 40000 km, bytt hver 120000 km

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Sjekk hver 500 km, bytt hver 12 måneder

SERVOSTYRING
Kapasitet: 0,9 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
ATF Dexron II-D

Sjekk hver 500 km

ALFA ROMEO (EU) 164 164 164 2.0 V6 TURBO (1991-1994)



KJØLESYSTEM

Kapasitet: 12,5 liter (Fabrikkpåfylling), Kapasitet: 10 liter (Servicepåfylling)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Sjekk hver 500 km, bytt hver 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.