

ALFA ROMEO (EU) 166 936 166 2.4 JTDM 20V (2003-2007)



MOTOR

Kapasitet: 5-5,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Specialsynth MSP 5W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Bytt hver 20000 km

TRANSAKSEL AUTOMAT 4/1

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Sjekk hver 80000 km

TRANSAKSEL MANUELL 5/1

Kapasitet: 3,2 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Sjekk hver 80000 km

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Sjekk hver 500 km, bytt hver 60000 km/ 24 måneder

SERVOSTYRING

Kapasitet: 1,4 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Sjekk hver 20000 km

ALFA ROMEO (EU) 166 936 166 2.4 JTDM 20V (2003-2007)



KJØLESYSTEM

Kapasitet: 9,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Sjekk hver 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.