

# ALFA ROMEO (EU) 75 162B 75 1.8 TURBO (1986-1991)



## MOTOR

Kapasitet: 5,6 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Classic Racing Oil 15W-50**

*Bytt hver 10000 km/ 6 måneder*

## TRANSAKSEL MANUELL 5/1

Kapasitet: 2,3 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**SP Gear 1011**

#### PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

#### PRODUKTANBEFALING 3

**Syngear 75W-90**

*Sjekk hver 20000 km, bytt hver 40000 km/ 24 måneder*

## HYDRAULISK BREMSESYSTEM

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

#### PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

*Bytt hver 12 måneder*

## HYDRAULISK CLUTCH-SYSTEM

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

#### PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

## SERVOSTYRING

Kapasitet: 0,8 liter

### BRUK

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**ATF Dexron II-D**

*Sjekk hver 20000 km/ 12 måneder*

# ALFA ROMEO (EU) 75 162B 75 1.8 TURBO (1986-1991)



## KJØLESYSTEM

Kapasitet: 8 liter

### BRUK

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

Bytt hver 40000 km/ 48 måneder

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*