

ALFA ROMEO (EU) 90 162 90 2.0I (1984-1988)



MOTOR

Kapasitet: 5,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

HDX 20W-50

Bytt hver 10000 km/ 6 måneder

TRANSAKSEL MANUELL 5/1

Kapasitet: 2,3 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Sjekk hver 20000 km, bytt hver 40000 km/ 24 måneder

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Bytt hver 12 måneder

HYDRAULISK CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Sjekk hver 10000 km/ 6 måneder

ALFA ROMEO (EU) 90 162 90 2.0I (1984-1988)



SMØREPUNKTER/NIPLER HJULLAGERE FORAN

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

Bytt hver 40000 km/ 48 måneder

KJØLESYSTEM

Kapasitet: 8 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Bytt hver 40000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.