

ALFA ROMEO (EU) SPIDER 916 SPIDER 3.0 V6 (1995-2003)



MOTOR AR 16101
Kapasitet: 5,9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol Racing 10W-60

PRODUKTANBEFALING 2

Emperol 10W-40

Sjekk hver 500 km, bytt hver 20000 km/ 12 måneder

BRUK

Normal

KLIMA

Arktis

PRODUKTANBEFALING 1

Duranza LSP 5W-30

PRODUKTANBEFALING 2

Asyntho 5W-30

Sjekk hver 500 km, bytt hver 20000 km/ 12 måneder

TRANSAKSEL MANUELL 5/1

Kapasitet: 2 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

SP Gear 1071

Sjekk hver 80000 km/ 48 måneder

HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC

Kapasitet: 0,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Sjekk hver 20000 km/ 12 måneder

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Sjekk hver 500 km, bytt hver 60000 km/ 24 måneder

ALFA ROMEO (EU) SPIDER 916 SPIDER 3.0 V6 (1995-2003)



SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Sjekk hver 500 km

KJØLESYSTEM

Kapasitet: 11,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Sjekk hver 500 km, bytt hver 80000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.