

ALFA ROMEO (EU) SPIDER 939 SPIDER 1750 TURBO (2009-2011)



MOTOR 939B1000

Kapasitet: 5 liter

BRUK

Fleksibel (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Specialsynth MSP 5W-40

Bytt hver 35000 km

TRANSAKSEL MANUELL 6/1

Kapasitet: 2 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Sjekk hver 35000 km

GIRBETJENINGSSYSTEM Selespeed

Kapasitet: 0,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Sjekk hver 35000 km

HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Sjekk hver 35000 km

HYDRAULISK BREMS/CLUTCHSYSTEM ABS

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Bytt hver 35000 km/ 24 måneder

ALFA ROMEO (EU) SPIDER 939 SPIDER 1750 TURBO (2009-2011)



SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Sjekk hver 35000 km

KJØLESYSTEM

Kapasitet: 6,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Sjekk hver 35000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.