

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4 (2006-2008)



MOTOR 939A000
Kapasitet: 5,4 liter

BRUK

Fleksibel (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

Bytt hver 30000 km

DIFFERENSIAL BAK
Kapasitet: 0,75 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Syngear 75W-90

Bytt hver 120000 km

OVERFØRINGSBOKS
Kapasitet: 0,6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Syngear 75W-90

Bytt hver 120000 km

TRANSAKSEL AUTOMAT Aisin Warner AF 40-6 6/1
Kapasitet: 6,1 liter (Påfylling fra helt tom), Kapasitet: 3,3 liter (Servicepåfylling)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Sjekk hver 30000 km

TRANSAKSEL MANUELL 6/1
Kapasitet: 2,8 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Sjekk hver 30000 km

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4(2006-2008)



HYDRAULIC SYSTEM (ROOF) ELECTRONIC/HYDRAULIC

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		
Sjekk hver 30000 km		

HYDRAULISK BREMS/CLUTCHSYSTEM ABS

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Sjekk hver 30000 km, bytt hver 60000 km		

SERVOSTYRING

Kapasitet: 1,3 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		
Sjekk hver 30000 km		

KJØLESYSTEM

Kapasitet: 10,3 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Sjekk hver 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.