

ARO 24 24 2.7 D (1984-2006)



MOTOR Aro L27
Kapasitet: 5,6 liter

BRUK	KLIMA
Normal	Fra Middelhavet

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

Bytt hver 5000 km

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Emperol 10W-40	

Bytt hver 5000 km

DIFFERENSIAL BAK
Kapasitet: 1,7 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Bytt hver 30000 km/ 36 måneder

DIFFERENSIAL FORAN (4x4)
Kapasitet: 1 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Bytt hver 30000 km/ 36 måneder

GIR MANUELL 4/1
Kapasitet: 2,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Bytt hver 30000 km/ 36 måneder



OVERFØRINGSBOKS

Kapasitet: 1,25 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Bytt hver 30000 km/ 36 måneder

HYDRAULISK BREMSESYSTEM

Kapasitet: 0,75 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Bytt hver 20000 km/ 24 måneder

SERVOSTYRING

Kapasitet: 3 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF-A

Bytt hver 50000 km

KJØLESYSTEM

Kapasitet: 13,25 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Bytt hver 20000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.