

AUDI (EU) A3, S3, RS 3 8V A3 1.4 TFSI (103 KW) (2013-2017)



MOTOR CPTA
Kapasiteit: 4,5 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Bytt hver 15000 km/ 12 måneder

BRUK
Fleksibel (maks)

KLIMA
Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Bytt hver 30000 km/ 24 måneder

TRANSAKSEL MANUELL 02S 6/1
Kapasiteit: 2,3 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

TRANSAKSEL SEMIAUTOMATISK S TRONIC 0CW 7/1
Kapasiteit: 1,7 liter

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

HYDRAULISK IGANGSETTING GIRKASSE

BRUK
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

AUDI (EU) A3, S3, RS 3 8V A3 1.4 TFSI (103 KW) (2013-2017)



HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Bytt hver 24 måneder

KJØLESYSTEM

Kapasitet: 0-0 liter (mellom min. og max.)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Sjekk hver 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.