

AUDI (EU) A4, S4, RS 4 8E A4 2.0 TDI 16V (89 KW) (2006-2007)



MOTOR BVG

Kapasitet: 3,8 liter, Filterkapasitet: 0,5 liter

BRUK

Utvidet tømning (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Bytt hver 50000 km/ 24 måneder

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL CVT

Kapasitet: 1,3 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

TRANSAKSEL CVT 01J 1/1

Kapasitet: 7,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4016

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Bytt hver 24 måneder

AUDI (EU) A4, S4, RS 4 8E A4 2.0 TDI 16V (89 KW) (2006-2007)



SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Sjekk hver 50000 km/ 24 måneder

KJØLESYSTEM

Kapasitet: 6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.