

AUDI (EU) A5, S5, RS 5 8T A5 3.0 TFSI QUATTRO (200 KW) (2011-2016)



MOTOR CHMB, CMUA, CRED
Kapasitet: 6,4 liter

BRUK

Utvidet tømning (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

Bytt hver 30000 km/ 24 måneder

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK 0BC
Kapasitet: 0,9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 24 måneder/ 30000 km

DIFFERENSIAL BAK 0BF
Kapasitet: 0,9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

DIFFERENSIAL BAK UTLØSING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

AUDI (EU) A5, S5, RS 5 8T A5 3.0 TFSI QUATTRO (200 KW) (2011-2016)



TRANSMISSION S TRONIC CLUTCH PART 0B5 (DL501)

Kapasitet: 6,7 liter (Servicepåfylling), Kapasitet: 7,5 liter (Tørr fyll, med oljekjølør), Kapasitet: 7 liter (Tørrfylling uten oljekjølør)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2072		

TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) 7/1

Kapasitet: 4,35 liter (Påfylling fra helt tom)

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2072		

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Bytt hver 24 måneder

KJØLESYSTEM

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Sjekk hver 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.