

AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TFSI QUATTRO (155 KW) CAEB (2009-2010)

**MOTOR CAEB, CPMA**

Kapasitet: 4,6 liter (Servicepåfylling)

BRUK	KLIMA
Utvidet tømning (maks)	Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

Bytt hver 30000 km/ 24 måneder

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK OBD

Kapasitet: 1 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90**DIFFERENSIAL FRA AUTOMAT**

Kapasitet: 1,1 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90**GIR AUTOMAT OB6 6/1**

Kapasitet: 9-10,4 liter (Påfylling fra helt tom)

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 2034

AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TFSI QUATTRO (155 KW) CAEB (2009-2010)



OVERFØRINGSBOKS FRA AUTOMATISK

Kapasitet: 0,5 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear LS 1015		

HYDRAULISK AKTIVERING CABRIOLET-TAK

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Bytt hver 24 måneder

SERVOSTYRING

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Sjekk hver 24 måneder/ 30000 km

KJØLESYSTEM

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Sjekk hver 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.