

AUDI (EU) A6 ALLROAD 4F A6 ALLROAD 3.0 TDI (176 KW) (2008-2011)



MOTOR CDYA, CDYC

Kapasitet: 8,2 liter (Servicepåfylling)

BRUK

Utvidet tømning (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Bytt hver 30000 km/ 24 måneder

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK OAR

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 24 måneder/ 30000 km

DIFFERENSIAL FRA AUTOMAT

Kapasitet: 1,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

OVERFØRINGSBOKS FRA AUTOMATISK

Kapasitet: 0,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear LS 1015

Sjekk hver 24 måneder/ 30000 km

AUDI (EU) A6 ALLROAD 4F A6 ALLROAD 3.0 TDI (176 KW) (2008-2011)



TRANSAKSEL AUTOMAT 09L 6/1

Kapasitet: 9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2034

Sjekk hver 24 måneder/ 30000 km

TRANSAKSEL MANUELL/OVERFØRINGSBOKS 0A3 6/1

Kapasitet: 3,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Bytt hver 24 måneder

SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KJØLESYSTEM

Kapasitet: 0-0 liter (mellom min. og max.)

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.