

AUDI (EU) A6 ALLROAD 4F A6 ALLROAD 4.2 FSI (2006-2010)



MOTOR BVJ

Kapasitet: 8,5 liter (Servicepåfylling)

BRUK		KLIMA
Utvidet tømning (maks)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Bytt hver 30000 km/ 24 måneder

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Bytt hver 15000 km/ 12 måneder

BRUK		KLIMA
Normal		Kaldt
PRODUKTANBEFALING 1		
Presteza MSP 5W-30		

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK 0AR

Kapasitet: 0,9 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Sjekk hver 24 måneder/ 30000 km

DIFFERENSIAL FRA AUTOMAT

Kapasitet: 1,1 liter

BRUK		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Sjekk hver 24 måneder/ 30000 km

AUDI (EU) A6 ALLROAD 4F A6 ALLROAD 4.2 FSI (2006-2010)



OVERFØRINGSBOKS FRA AUTOMATISK

Kapasitet: 0,5 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear LS 1015		

Sjekk hver 24 måneder/ 30000 km

TRANSAKSEL AUTOMAT 09L 6/1

Kapasitet: 9 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2034		

Sjekk hver 24 måneder/ 30000 km

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Bytt hver 24 måneder

SERVOSTYRING

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

KJØLESYSTEM

Kapasitet: 12 liter

BRUK	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.