

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)



MOTOR

Kapasitet: 5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Bytt hver 15000 km/ 12 måneder

BRUK

Normal

KLIMA

Kaldt

PRODUKTANBEFALING 1

Emperol 5W-40

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL BAK

Kapasitet: 1,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

Sjekk hver 15000 km/ 12 måneder

DIFFERENSIAL FRA AUTOMAT

Kapasitet: 0,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 15000 km/ 12 måneder

GIR AUTOMAT 4/1

Kapasitet: 2,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032

Sjekk hver 30000 km/ 12 måneder, bytt hver 60000 km/ 48 måneder

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)



TRANSAKSEL MANUELL 6/1

Kapasitet: 2,35 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 15000 km/ 12 måneder

TRANSAKSEL MANUELL/OVERFØRINGSBOKS 6/1

Kapasitet: 2,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 15000 km/ 12 måneder

HYDRAULIKKSYSTEM SERVOSTYRING/NIVÅREGULERING

Kapasitet: 2,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

HYDRAULISK BREMSE-/CLUTCH-SYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Bytt hver 24 måneder

SERVOSTYRING

Kapasitet: 1,1 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

AUDI (EU) A6, S6 4A A6 2.5 TDI QUATTRO (103 KW) (1995-1997)



KJØLESYSTEM

Kapasitet: 6,5 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Bytt hver 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.