

AUDI (EU) A6, S6, RS 6 4B A6 2.5 TDI V6 (132 KW) (2000-2005)



MOTOR AKE, BAU, BDH
Kapasitet: 5,5 liter (Servicepåfylling)

BRUK

Utvidet tømning (maks)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Bytt hver 35000 km/ 24 måneder

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Bytt hver 15000 km/ 12 måneder

BRUK

Normal

KLIMA

Kaldt

PRODUKTANBEFALING 1

Emperol 5W-40

Bytt hver 15000 km/ 12 måneder

DIFFERENSIAL FRA AUTOMAT

Kapasitet: 0,8 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 70000 km

GIR AUTOMAT 01V 5/1

Kapasitet: 9 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032

Sjekk hver 35000 km

AUDI (EU) A6, S6, RS 6 4B A6 2.5 TDI V6 (132 KW) (2000-2005)

**TRANSAXSEL MANUELL 6/1**

Kapasitet: 2,7 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Sjekk hver 35000 km

HYDRAULISK BREMSESYSTEM

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Bytt hver 24 måneder

SERVOSTYRING

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013**KJØLESYSTEM**

Kapasitet: 6 liter

BRUK

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.